



PORTABLE MAGNETIC DRILLS

		HMD115	HMD150	HMD904	HMD925	HMD914	HMD505 / HMD508	HMD915
		Low Profile		Fabricating			Heavy Duty Drilling	
Annular Cutters	RotaLoc™	✓	✓	With Adapter	With Adapter	With Adapter	With Adapter	
	RotaLoc Plus™		✓	With Adapter	With Adapter	With Adapter	With Adapter	
	Rotabroach® "12,000-Series"			✓	✓	✓	✓	With Adapter (3/4" & Larger)
	Copperhead™ Carbide Tipped			✓	✓	✓	✓	
	Rotabroach® "42/43,000-Series"							✓
Model Specifications	Diameter Min./Max.	1/2" to 1-1/16" (12 - 27mm)	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-1/2" (1-1/4" Pwr. Fd.) (12 - 38mm) (32mm Pwr Fd.)	7/16" to 2-1/16" (12 - 52mm)	7/16" to 2-3/8" (12 - 60mm)	3/4" to 3-1/16" (19 - 77mm)
	Depth Max.	3/4" (19mm)	1" (25mm)	2" (50mm)	2" (50mm)	3" (76mm)	3" (76mm)	3" (76mm)
	Cutter Mounting	Bayonet Style	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" or 1-1/4" Weldon Shank
	No-Load R.P.M.	450	450	450	450	350	250 / 450 450 / 750	120 / 332 (w/ gear swap)
	Model Weight	21.3 lbs (9.7 kg)	22.7 lbs (10.3 kg)	27.5 lbs (12.5 kg)	37 lbs (16.8 kg)	41 lbs (18.6 kg)	45 lbs (20.4 kg)	69 lbs (31.3 kg)
	Thru-the-Tool Coolant			✓	✓	✓	✓	✓
Available Accessories	Carrying Case Included	✓	✓	✓	Optional	✓	✓	
	Swivel Base			Optional	Optional	Optional		
	Pipe Adapter			✓	Manual Mode	✓	✓	Bracket Mount
	Tap Attachment			✓	Manual Mode	✓		
	Vac-Pad™			✓				
	Coolant Bottle			Optional	Included	Included	Included	Included
	Countersink Kit			✓	Manual Mode	✓	✓	With Adapter
	Twist Drill Adapter			✓	Manual Mode	✓	✓	With Adapter
	Ratchet Drive	✓	✓	✓			✓	
	Arbor Extender			✓	Manual Mode	✓	✓	With Adapter
	Drill Chuck			✓	Manual Mode	✓		
	RotaLoc™ Spindle Adapter			✓	Manual Mode	✓	✓	